# Canon

## **CX-G6400** Card & Badge Printer

FAST AND VERSATILE, FOR VIBRANT, HIGH-RESOLUTION ON-DEMAND CARD AND BADGE PRINTING

The Canon CX-G6400 card & badge printer is designed to easily produce customized photo-quality images on four-inch single-sided paper and CR80 plastic cards with speed and efficiency.



#### WIDE VARIETY OF USES

Engineered for speed and capable of oversized high-quality output, the CX-G6400 printer is ideal to produce single-sided paper or CR80 plastic cards in vibrant color. For concert badges, press passes, event badges, oversized passes, business cards, and envelopes, the printer can deliver the professional look needed in sectors like entertainment, hospitality, retail, administrative & support services, government and more. Printing cards on-demand allows users to print what is needed when it is needed, so there is no need to maintain a large inventory.

#### **HIGH PERFORMANCE**

The CX-G6400 printer is fast and can print up to 45 single-sided paper or plastic cards per minute, with a first-print-out time of approximately 12 seconds or less<sup>1</sup>. With a feed hopper of up to 400 paper or plastic cards / 100 envelopes and the ability to refill while printing, performance is maximized.

#### EASY TO INSTALL AND USE

The CX-G6400 printer has a small, compact footprint, allowing it to easily be installed on a desktop or counter. The straightforward operation buttons make the printer simple to use. Also, the CX-G6400 uses inkjet printer cartridges that are easy to replace. Plus, it supports dual media printing, able to handle printing on plastic or paper.

#### **OUTSTANDING PRINT QUALITY**

The CX-G6400 printer produces professional-looking crisp and clear photo-quality images, with up to 1200 x 1200 dpi resolution, making text, images, and scan codes look sharp and crisp. The printer also uses dye-based inkjet printing, for vivid and vibrant color output.

#### **CUSTOMER CARE**

For investment protection, eCarePAK extended service plan<sup>2</sup> options are available beyond the initial two-year on-site limited warranty period. An eCarePAK can help save on costs associated with post-purchase maintenance and help maximize uptime throughout the product life.

 Based upon standard business card print conditions with no image and print size of 2"x3.5" inkjet coated matte business card, 7.5% Duty/Color, 100 sheets x 3 jobs/day. Print speed can vary based on click to drop, average print coverage, with USB connectivity.
 Warranty and Support programs are subject to certain conditions and restrictions. See usa.canon.com/support for details.





Canon Specialty Printer Medical Center TED E. BEAR Visior Maternity Ward 2:29 PM Friday, Rovember 10, 2017





#### **TECHNICAL SPECIFICATIONS**

Maximum Print Speed1(64/32 bit), Windows Server 2012 (64-bit),First Print Out Time Approximately 12 seconds or LessWindows Server 2008 (64-bit),Business Card 100 Cards/minute (6,000 Cards Per Hour)Operating EnvironmentPlastic Card (CR80) 90 Cards/minute (5,400 Cards Per Hour)Temperature 41° - 95°F (5° - 35°C)4"x6" Postcard 45 Cards/minute (2,700 Cards Per Hour)Humidity 10 - 90% RH (Non-Condensing)Envelope 28 Envelopes/minuteChemical SafetyTSCA, OSHA HCSSupported Media TypesPower ConsumptionPlastic Card 2" x 3.5" PVC (CR80, CR100)Operating Approx. 229 WCustom Size Paper/Plastic wtihin Maximum Printable Size & Up to 30 milSleep Mode Approx. 8.5 W or LessMaximum MediaAcoustic Information4Capacity2Operating Noise (Max.) 58dB or lessPlastic & Paper Card 400 CardsStandby Noise 35dB or lessPlastic & Paper Card 400 CardsStandby Noise 35dB or lessPlastic & Paper Card 400 CardsStandby Noise 35dB or lessPlastic & Paper Card 400 CardsStandby Noise 35dB or lessPlastic & Paper Card 400 CardsStandby Noise 35dB or lessSupported Media SizeDimensions & Weight <sup>6</sup> & ThicknessDimensions & Weight <sup>6</sup>	<b>PRINTER SPECIFICA</b>	TIONS	GENERAL	
Print Resolution1200 x 1200 dpiPrint ModeSingle Sided (Simplex)Number of Nozzles5,185 dotsMumber of Nozzles5,185 dotsMaximum Print Speed'ConnectivityUSB 2.0, Ethernet (10/100/100 Base-T)Maximum Print Speed'(64/32 bit), 8.1 (64/32 bit), 7.51First Print Out Time Approximately 12 seconds or LessWindows Server 2008 (64-bit)Business Card 100 Cards/minute (6,000 Cards Per Hour)Operating EnvironmentPlastic Card (CR80) 90 Cards/minute (2,700 Cards Per Hour)Temperature 41° - 95°F (5° - 35°C)4"x6" Postcard 45 Cards/minute (2,700 Cards Per Hour)Chemical SafetyPaper Card Business Card, Credential, Envelope, PostcardMaximum Approx. 229 WPlastic Card 2" x 3.5" PVC (CR80, CR100)Cuercing Approx. 135 WCustom Size Paper/Plastic within Maximum Printable Size & Up to 30 milSleep Mode Approx. 8.5 W or LessMaximum MediaCoparating Noise (Max.) 58dB or lessPlastic & Paper Card 400 CardsStandby Noise 35dB or lessPlastic & Paper Card 400 CardsStandby Noise 35dB or lessPlastic & Paper Card 400 CardsStandby Noise 35dB or lessPlastic & Paper Card 400 CardsStandby Noise 35dB or lessSupported Media SizeDimensions & Weight <sup>6</sup> 23.4" (W) x 16.1" (D) x 18.3" (H) / 55.1 lbs.Supported Media SizeDimensions & Canon CX-66400 Inkjet Card Printer	Print Method	Dye-based Inkjet	Operational Method	
Print Mode       Single Sided (Simplex)         Number of Nozzles       5,185 dots         Number of Nozzles       5,185 dots         Maximum Print Speed'       USB 2.0, Ethernet (10/100/100 Base-T)         Maximum Print Speed'       USB 2.0, Ethernet (10/100/100 Base-T)         Business Card       100 Cards/minute (6,000 Cards Per Hour)         Plastic Card (CR80)       90 Cards/minute (6,000 Cards Per Hour)         Plastic Card (CR80)       90 Cards/minute (5,400 Cards Per Hour)         4"x6" Postcard       45 Cards/minute (2,700 Cards Per Hour)         Envelope       28 Envelopes/minute         Supported Media Types       Humidity 10 - 90% RH (Non-Condensing)         Paper Card Business Card, Credential, Envelope, Postcard       Maximum Approx. 229 W         Plastic Card 2" x 3.5" PVC (CR80, CR100)       Operating Approx. 35 W or Less         & Up to 30 mil       Sleep Mode Approx. 85 W or Less         & Up to 30 mil       Capacity²         Plastic & Paper Card 400 Cards       Standby Noise 35dB or less         Envelope 100 Envelopes       Standby Noise 35dB or less         Supported Media Size       Warranty <sup>6</sup> Two-Year On-Site Limited Warranty         Supported Media Size       Dimensions & Weight <sup>6</sup> 23.4" (W) x 16.1" (D) x 18.3" (H) / 55.1 lbs.         Supported Media Size       Box C	Ink Cartridges	4 (1 x Black, 1 x Cyan, 1 x Magenta, 1 x Yellow)	LCD No	
Number of Nozzles5,85 dotsOS Compatibility3Windows 10 (64/32 bit), 8.10 (64/32 bit), 7 SI (64/32 bit), Windows Server 2012 (64-bit), (64/32 bit), Windows Server 2012 (64-bit), (64/32 bit), Windows Server 2012 (64-bit), (64/32 bit), Windows Server 2012 (64-bit), Windows Server 2018 (64-bit)Plastic Card (CR80) Paper Card Business Card, Credential, Envelope, Postcard Plastic Card 2" x 3.5" PVC (CR80, CR100)Chemical Safety Power ConsumptionPaper Card Plastic Card 2" x 3.5" PVC (CR80, CR100)Maximum Approx. 229 W Operating Approx. 135 WCustom Size Paper/Plastic wthin Maximum Printable Size & Up to 30 milElectrical AC 100-240V, 50/60HzMaximum Media Capacity2Custom Size Plastic & Paper Card 100 EnvelopesStandby Noise Standby Noise 35dB or lessPlastic & Paper Card Business Card d00 CardsStandby Noise Standby Noise Standby Noise 35dB or lessPlastic & Paper Card BusinessWore Card S Standby Noise Standby Noise 35dB or lessPlastic & Paper Card BusinessWindows Cards Standby Noise Standby Noise 35dB or lessPlastic & Paper Card BusinessWindows Cards Standby Noise Standby Noise 35dB or lessPlastic & Paper Card BusinessMaximum Printable SizePlastic & Paper Card BusinessMaximum Printable SizePlastic & Paper Card <b< th=""><th>Print Resolution</th><th>1200 x 1200 dpi</th><th colspan="2">Buttons/LEDs 3 Buttons / 8 LEDs</th></b<>	Print Resolution	1200 x 1200 dpi	Buttons/LEDs 3 Buttons / 8 LEDs	
Maximum Print Speed¹Comparing Approximately 12 seconds or Less Business Card 100 Cards/minute (6,000 Cards Per Hour)Comparing Approximately 12 seconds or Less Windows Server 2008 (64-bit)Plastic Card (CR80) 90 Cards/minute (5,400 Cards Per Hour)Operating EnvironmentTemperature 41° - 95°F (5° - 35°C)4"x6" Postcard 45 Cards/minute (2,700 Cards Per Hour)Temperature 41° - 95°F (5° - 35°C)Humidity 10 - 90% RH (Non-Condensing)Envelope 28 Envelopes/minuteChemical SafetyTSCA, OSHA HCSSupported Media TypesPaper Card Business Card, Credential, Envelope, PostcardMaximum Approx. 229 WPlastic Card 2" x 3.5" PVC (CR80, CR100)Operating Approx. 135 WCustom Size Paper/Plastic wtihin Maximum Printable Size & Up to 30 milElectricalAC 100-240V, 50/60HzMaximum MediaAcoustic Information4Acoustic Information4Capacity2Operating Noise (Max.) 58dB or lessPlastic & Paper Card 400 CardsStandby Noise 35dB or lessPlastic & Paper Card 400 CardsStandby Noise 35dB or lessEnvelope 100 EnvelopesWarranty5Two-Year On-Site Limited WarrantySupported Media Size & ThicknessDimensions & Weight <sup>6</sup> 23.4" (W) x 16.1" (D) x 18.3" (H) / 55.1 lbs.	Print Mode	Single Sided (Simplex)	Connectivity	USB 2.0, Ethernet (10/100/100 Base-T)
First Print Out Time Approximately 12 seconds or LessWindows Server 2008 (64-bit)Business Card 100 Cards/minute (6,000 Cards Per Hour)Operating EnvironmentPlastic Card (CR80) 90 Cards/minute (5,400 Cards Per Hour)Temperature 41° - 95°F (5° - 35°C)4"x6" Postcard 45 Cards/minute (2,700 Cards Per Hour)Humidity 10 - 90% RH (Non-Condensing)Envelope 28 Envelopes/minuteChemical SafetyTSCA, OSHA HCSSupported Media TypesPower ConsumptionPlastic Card 2" x 3.5" PVC (CR80, CR100)Operating Approx. 135 WCustom SizePaper/Plastic within Maximum Printable Size & Up to 30 milElectricalMaximum MediaAc 100-240V, 50/60HzCapacity2Operating Noise (Max.)58dB or lessPlastic & Paper Card 400 CardsStandby Noise35dB or lessPlastic & Paper Card 400 CardsStandby Noise35dB or lessPlastic & Paper Card 400 CardsStandby Noise35dB or lessPlastic & Supported Media SizeStandby Noise35dB or lessPlastic & Supported Media SizeStandby Noise35dB or lessPlastic & Paper Card 400 CardsStandby Noise35dB or lessPlastic & Paper Card 400 CardsStandby Noise35dB or lessPlastic & Supported Media SizeSupported Media SizeSupported Media SizeStandby NoiseBusinessSupported Media SizeSupported Media SizeStandby Noise23.4" (W) x 16.1" (D) x 18.3" (H) / 55.1 lbs.Box ContentsCanon CX-G6400 Inkjet Card Printer	Number of Nozzles	5,185 dots	OS Compatibility <sup>3</sup>	Windows 10 (64/32 bit), 8.1 (64/32 bit), 7 SP1
Business Card 100 Cards/minute (6,000 Cards Per Hour)Operating EnvironmentPlastic Card (CR80) 90 Cards/minute (5,400 Cards Per Hour)Temperature 41° - 95°F (5° - 35°C)4"x6" Postcard 45 Cards/minute (2,700 Cards Per Hour)Humidity 10 - 90% RH (Non-Condensing)4"x6" Postcard 45 Cards/minute (2,700 Cards Per Hour)Humidity 10 - 90% RH (Non-Condensing)Envelope 28 Envelopes/minuteChemical SafetyTSCA, OSHA HCSSupported Media TypesPover ConsumptionPover ConsumptionPaper Card Business Card, Credential, Envelope, PostcardMaximum Approx. 229 WPlastic Card 2" x 3.5" PVC (CR80, CR100)Operating Approx. 135 WCustom Size Paper/Plastic within Maximum Printable SizeSleep Mode Approx. 8.5 W or Less& Up to 30 milElectricalAC 100-240V, 50/60HzMaximum MediaOperating Noise (Max.)58dB or lessPlastic & Paper Card 400 CardsStandby Noise35dB or lessPlastic & Paper 100 EnvelopesWarranty <sup>5</sup> Two-Year On-Site Limited WarrantySupported Media SizeDimensions & Weight <sup>6</sup> 2.3.4" (W) x 16.1" (D) x 18.3" (H) / 55.1 lbs.& ThicknessCanon CX-G6400 Inkjet Card Printer	Maximum Print Speed <sup>1</sup>			(64/32 bit), Windows Server 2012 (64-bit),
Plastic Card (CR80) 90 Cards/minute (5,400 Cards Per Hour)       Temperature 41° - 95°F (5° - 35°C)         4"x6" Postcard 45 Cards/minute (2,700 Cards Per Hour)       Humidity 10 - 90% RH (Non-Condensing)         Envelope 28 Envelopes/minute       Chemical Safety       TSCA, OSHA HCS         Supported Media Types       Power Consumption       Power Consumption         Paper Card Business Card, Credential, Envelope, Postcard       Maximum Approx. 229 W       Operating Approx. 135 W         Plastic Card 2" x 3.5" PVC (CR80, CR100)       Operating Approx. 135 W       Sleep Mode Approx. 8.5 W or Less         & Up to 30 mil       Electrical       AC 100-240V, 50/60Hz         Maximum Media       Acoustic Information <sup>4</sup> SdB or less         Plastic & Paper Card 400 Cards       Standby Noise (Max.)       5dB or less         Plastic & Paper Card 400 Cards       Standby Noise (Max.)       5dB or less         Supported Media Size       Supported Media Size       Two-Year On-Site Limited Warranty         Supported Media Size       Dimensions & Weight <sup>6</sup> 23.4" (W) x 16.1" (D) x 18.3" (H) / 55.1 lbs.         Box Contents       Canon CX-G6400 Inkjet Card Printer	First Print Out Time	Approximately 12 seconds or Less		Windows Server 2008 (64-bit)
4"x6" Postcard 45 Cards/minute (2,700 Cards Per Hour)       Humidity 10 - 90% RH (Non-Condensing)         Envelope 28 Envelopes/minute       Chemical Safety       TSCA, OSHA HCS         Supported Media Types       Power Consumption       Power Consumption         Paper Card Business Card, Credential, Envelope, Postcard       Maximum Approx. 229 W       Operating Approx. 135 W         Plastic Card 2" x 3.5" PVC (CR80, CR100)       Operating Approx. 135 W       Electrical         & Up to 30 mil       Electrical       AC 100-240V, 50/60Hz         Maximum Media       Acoustic Information <sup>4</sup> Coperating Noise (Max.) 58dB or less         Plastic & Paper Card 400 Cards       Standby Noise 35dB or less       Standby Noise 35dB or less         Plastic & Paper Card 400 Cards       Varranty <sup>6</sup> Two-Year On-Site Limited Warranty         Supported Media Size       Dimensions & Weight <sup>6</sup> 23.4" (W) x 16.1" (D) x 18.3" (H) / 55.1 lbs.         & Thickness       Canon CX-G6400 Inkjet Card Printer	Business Card	100 Cards/minute (6,000 Cards Per Hour)	<b>Operating Environment</b>	
Envelope28 Envelopes/minuteChemical SafetyTSCA, OSHA HCSSupported Media TypesPower ConsumptionPaper Card Business Card, Credential, Envelope, Postcard Plastic Card 2" x 3.5" PVC (CR80, CR100)Maximum Approx. 229 WPlastic Card 2" x 3.5" PVC (CR80, CR100)Operating Approx. 135 WCustom Size Paper/Plastic wtihin Maximum Printable Size & Up to 30 milSleep Mode Approx. 8.5 W or LessBaximum MediaAC 100-240V, 50/60HzCapacity2Operating Noise (Max.)Plastic & Paper Card 400 CardsStandby Noise 35dB or lessPlastic & Paper 100 EnvelopesWarranty5Supported Media Size & Two-Year On-Site Limited WarrantySupported Media Size & ThicknessDimensions & Weight6Supported Media Size & ThicknessDimensions & Weight6Supported Media Size & ThicknessDimensions & Weight6Supported Media SizeDimensions & Weight6Supported Media SizeCanon CX-G6400 Inkjet Card Printer	Plastic Card (CR80)	90 Cards/minute (5,400 Cards Per Hour)	<b>Temperature</b> 41° - 95°F (5° - 35°C)	
Supported Media TypesPower ConsumptionPaper Card Business Card, Credential, Envelope, PostcardMaximum Approx. 229 WPlastic Card 2" x 3.5" PVC (CR80, CR100)Operating Approx. 135 WCustom Size Paper/Plastic wtihin Maximum Printable Size & Up to 30 milSleep Mode Approx. 8.5 W or LessMaximum MediaAC 100-240V, 50/60HzCapacity²Operating Noise (Max.) 58dB or lessPlastic & Paper Card 400 CardsStandby Noise 35dB or lessEnvelope 100 EnvelopesWarranty5Two-Year On-Site Limited WarrantySupported Media Size & ThicknessDimensions & Weight <sup>6</sup> 23.4" (W) x 16.1" (D) x 18.3" (H) / 55.1 lbs.Box ContentsCanon CX-G6400 Inkjet Card Printer	4"x6" Postcard	45 Cards/minute (2,700 Cards Per Hour)	Humidit	<b>y</b> 10 - 90% RH (Non-Condensing)
Paper Card Business Card, Credential, Envelope, Postcard Plastic Card 2" x 3.5" PVC (CR80, CR100)Maximum Approx. 229 WCustom Size Paper/Plastic wtihin Maximum Printable Size & Up to 30 milOperating Approx. 135 WCustom Size Paper/Plastic wtihin Maximum Printable Size & Up to 30 milElectricalAC 100-240V, 50/60HzMaximum MediaAc 100-240V, 50/60HzAcoustic Information4Capacity2 Plastic & Paper Card 400 CardsOperating Noise (Max.) 58dB or lessPlastic & Paper Card 400 CardsStandby Noise 35dB or lessEnvelope 100 EnvelopesWarranty5Two-Year On-Site Limited WarrantySupported Media Size & ThicknessDimensions & Weight623.4" (W) x 16.1" (D) x 18.3" (H) / 55.1 lbs.Box ContentsCanon CX-G6400 Inkjet Card Printer	Envelope	28 Envelopes/minute	Chemical Safety	TSCA, OSHA HCS
Plastic Card 2" x 3.5" PVC (CR80, CR100)Operating Approx. 135 WCustom Size Paper/Plastic wtihin Maximum Printable SizeSleep Mode Approx. 8.5 W or Less& Up to 30 milElectricalMaximum MediaAC 100-240V, 50/60HzCapacity²Operating Noise (Max.) 58dB or lessPlastic & Paper Card 400 CardsStandby Noise 35dB or lessPlastic & Paper 100 EnvelopesWarranty <sup>5</sup> Two-Year On-Site Limited WarrantySupported Media SizeDimensions & Weight <sup>6</sup> 23.4" (W) x 16.1" (D) x 18.3" (H) / 55.1 lbs.& ThicknessGanon CX-G6400 Inkjet Card Printer	Supported Media Types	;	Power Consumption	
Custom Size Paper/Plastic wtihin Maximum Printable Size       Sleep Mode Approx. 8.5 W or Less         & Up to 30 mil       Electrical       AC 100-240V, 50/60Hz         Maximum Media       Acoustic Information <sup>4</sup> Capacity <sup>2</sup> Operating Noise (Max.) 58dB or less         Plastic & Paper Card 400 Cards       Standby Noise 35dB or less         Envelope 100 Envelopes       Warranty <sup>5</sup> Supported Media Size       Dimensions & Weight <sup>6</sup> & Thickness       Canon CX-G6400 Inkjet Card Printer	Paper Card	Business Card, Credential, Envelope, Postcard	Maximun	n Approx. 229 W
& Up to 30 mil     Electrical     AC 100-240V, 50/60Hz       Maximum Media     Acoustic Information <sup>4</sup> Capacity <sup>2</sup> Operating Noise (Max.) 58dB or less       Plastic & Paper Card 400 Cards     Standby Noise 35dB or less       Envelope 100 Envelopes     Warranty <sup>5</sup> Two-Year On-Site Limited Warranty       Supported Media Size     Dimensions & Weight <sup>6</sup> 23.4" (W) x 16.1" (D) x 18.3" (H) / 55.1 lbs.       & Thickness     Box Contents     Canon CX-G6400 Inkjet Card Printer	Plastic Card	2" x 3.5" PVC (CR80, CR100)	Operating	g Approx. 135 W
Maximum Media     Acoustic Information <sup>4</sup> Capacity <sup>2</sup> Operating Noise (Max.) 58dB or less       Plastic & Paper Card 400 Cards     Standby Noise 35dB or less       Envelope 100 Envelopes     Warranty <sup>5</sup> Two-Year On-Site Limited Warranty       Supported Media Size     Dimensions & Weight <sup>6</sup> 23.4" (W) x 16.1" (D) x 18.3" (H) / 55.1 lbs.       & Thickness     Box Contents     Canon CX-G6400 Inkjet Card Printer	Custom Size	Paper/Plastic wtihin Maximum Printable Size	Sleep Mode	e Approx. 8.5 W or Less
Capacity <sup>2</sup> Operating Noise (Max.) 58dB or less       Plastic & Paper Card 400 Cards     Standby Noise 35dB or less       Envelope 100 Envelopes     Warranty <sup>5</sup> Two-Year On-Site Limited Warranty       Supported Media Size     Dimensions & Weight <sup>6</sup> 23.4" (W) x 16.1" (D) x 18.3" (H) / 55.1 lbs.       & Thickness     Box Contents     Canon CX-G6400 Inkjet Card Printer		& Up to 30 mil	Electrical	AC 100-240V, 50/60Hz
Plastic & Paper Card 400 Cards     Standby Noise 35dB or less       Envelope 100 Envelopes     Warranty <sup>5</sup> Two-Year On-Site Limited Warranty       Supported Media Size     Dimensions & Weight <sup>6</sup> 23.4" (W) x 16.1" (D) x 18.3" (H) / 55.1 lbs.       & Thickness     Box Contents     Canon CX-G6400 Inkjet Card Printer			Acoustic Information <sup>4</sup>	
Envelope 100 Envelopes     Warranty <sup>5</sup> Two-Year On-Site Limited Warranty       Supported Media Size     Dimensions & Weight <sup>6</sup> 23.4" (W) × 16.1" (D) × 18.3" (H) / 55.1 lbs.       & Thickness     Box Contents     Canon CX-G6400 Inkjet Card Printer			Operating Noise (Max.) 58dB or less	
Supported Media Size       Dimensions & Weight <sup>6</sup> 23.4" (W) x 16.1" (D) x 18.3" (H) / 55.1 lbs.         & Thickness       Box Contents       Canon CX-G6400 Inkjet Card Printer	Plastic & Paper Card 400 Cards		Standby Noise 35dB or less	
& Thickness       Box Contents       Canon CX-G6400 Inkjet Card Printer	Envelope	100 Envelopes	Warranty⁵	Two-Year On-Site Limited Warranty
	Supported Media Size		Dimensions & Weight <sup>6</sup>	23.4" (W) x 16.1" (D) x 18.3" (H) / 55.1 lbs.
			Box Contents	Canon CX-G6400 Inkjet Card Printer
	Media Size			Head Package Unit
Length: 49.0 - 300 mm / 1.9" - 11.8" Power Cord		Length: 49.0 - 300 mm / 1.9" - 11.8"		Power Cord
Media Thickness Paper/Plastic: 0.21 - 0.76 mm / 8.27 - 30 mil Set of Ink Tanks (BK, C, M, Y, 105 ml/each)	Media Thickness	Paper/Plastic: 0.21 - 0.76 mm / 8.27 - 30 mil		Set of Ink Tanks (BK, C, M, Y, 105 ml/each)
Envelope: 0.24 - 0.48 mm / 9.45 - 18.9 mil Maintenance Cartridge (Installed)		Envelope: 0.24 - 0.48 mm / 9.45 - 18.9 mil		Maintenance Cartridge (Installed)
Maximum PrintableWidth: 107.8 mm / 4.2"Printer Driver/User Guide CD	Maximum Printable	Width: 107.8 mm / 4.2"		Printer Driver/User Guide CD
Size/Area         Length: 297.0 mm / 11.7"         Getting Started Guide & Unpacking	Size/Area	Length: 297.0 mm / 11.7"		Getting Started Guide & Unpacking
Minimum Margin         Top/Bottom: 1.5 mm         Instructions	Minimum Margin	Top/Bottom: 1.5 mm		Instructions
Left/Right: 2.0 mm Installation Adjustment Paper (Postcard		Left/Right: 2.0 mm		Installation Adjustment Paper (Postcard
INK & MAINTENANCE CARTRIDGE INFORMATION	INK & MAINTENANC			Size)
Output per Cartridge         Approx. 24,000 Cards         Warranty Card				Warranty Card
Set <sup>1</sup>				

 Cartridge Fill Volume
 Black / Cyan / Magenta / Yellow: 105 ml

 Maintenance Cartridge
 WT-X201 Maintenance Cartridge

 Info & Fill Volume<sup>1</sup>
 Approx. 72,000 Cards

#### **PRINTER INFORMATION**

CX-G6400

MODEL NUMBER

DESCRIPTION



I

CX-G6400 Card & Badge Printer

### 1749C002[AA]

#### SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

1. Based upon standard business card print conditions with no image and print size of 2"x3.5" inkjet coated matte business card, 7.5% Duty/Color, 100 sheets x 3 jobs/day. Print speed can vary based on click to drop, average print coverage, with USB connectivity

2. Based upon business card weight thickness measured at 300gsm (0.3mm)

3. Operation can only be guaranteed on a PC with pre-installed Windows® 10 (64/32-bit), Windows 8.1 (64/32-bit), Windows 7 (64/32-bit)

- 4. Acoustic noise is based off the measurement following ISO7779, and the display number shall follow ISO9296
- 5. Warranty and support programs are subject to certain conditions and restrictions. See www.usa.canon.com/support for details

6. Printer weight measured excluding printhead or ink cartridges installed

Canon is a registered trademark of Canon Inc. in the United States, and may be a registered trademark or trademark in other countries.eCarePAK is a registered trademark of Canon U.S.A., Inc. in the United States. Pricing, specifications and availability subject to change without notice. Not responsible for typographical errors. Actual prices set by dealer/ reseller and may vary. ©2023 Canon U.S.A., Inc. All rights reserved.